

DESCRIPTION

S-9350 Glo-Kote™ is a glow-in-the-dark, thin-set overlayment, formulated to provide a light-reflected walking area or decorative finish at 1/8" thickness over any cement-based substrate. S-9350 Glo-Kote is a blend of non-radioactive photoluminescent aggregate polymers designed for concrete safety and decorative designs or overlays. This glow-in-the-dark overlay product is formulated to absorb ultra violet rays from the sun during daylight hours and casts a reflective glow during night hours. Two hours of direct sunlight exposure typically yields reflection for 8 to 12 hours.

USES

Glo-Kote is a versatile, easy-to-use material with a variety of uses in commercial, residential, and industrial applications. Glo-Kote can be applied by squeegee, broom, trowel or screed rake to create a multitude of textures and finishes.

Stairs	Safety
Anti-skid	Pool Decks
Emergency Exits and Entrances	Countertops
Driveways / Sidewalks / Curbs	Parking Decks
Decorative Overlays	Recreational Surfaces
Unique Design Element	Landscaping Projects
Heat Reflection and Absorption	Outdoor Entertainment Areas
Pedestrian and Vehicle Traffic Directives	Bars / Restaurants
Patios / Pathway	

Anywhere light reflection at night is desired for safety or a glow-in-the-dark effect is desired!



ADVANTAGES

S-9350 Glo-Kote is extremely versatile for any concrete resurfacing project where a renewable ambient light source is needed or desired.

Glow for up to 12 hours	Highly versatile
Environmentally friendly and safe	Water resistant
Non-toxic / non-reactive	Salt treatment resistant
Ready-mix formula - just add water	Fire resistant
Superior bonding capabilities	Non-reemulsifiable
Extreme climate resistance	Easily applied
Concrete repair and resurfacing abilities	Non-slip surface
Contributes to LEED credits EA1	
Renewable light source	

AVAILABILITY

Due to the special ingredients in this material, lead times may be extended. Please call for availability before beginning your project.

SURFACE PREPARATION

Surfaces that are to be repaired or coated must be structurally sound. Surface damage such as surface deterioration, cracks and spalls can typically be repaired. However, structural integrity is critical to the overall success of any coating or overlay. Remove any loose, soft or contaminated materials from the area that is to be repaired or resurfaced. Any existing coatings, sealers, curing agents, bond-breakers, etc. must be removed from the surface providing direct contact with the original substrate to assure adhesion. Typical preparation methods may include scraping, water blasting, sand blasting, shot blasting, cleaning and degreasing. **Note: All expansion joints must be honored.** Clean, repair and honor all control joints and expansion joints during entire application process, or mark them for honoring after application. Clean and treat all cracks and spalls in accordance with manufacturer's specifications.

Important: S-9350 Glo-Kote is designed to penetrate the surface for a permanent bond. Any sealers or coatings which will interfere with this penetration must be removed prior to application. The surface shall be cleaned thoroughly of all contamination by scrubbing the surface with S-12000 Heavy Duty Degreaser™. Spray S-12000 Heavy Duty Degreaser over the entire surface and allow it to dwell on the surface for approximately 15-30 minutes then, completely rinse with clean water two times.

Extremely oily surfaces can be pre-heated with a propane torch to bring the oil to the surface, followed by degreasing and water-blasting. Repeat this process until the surface is free of oily substances.

Arizona Polymer Flooring recommends that all Super-Krete cementitious overlay product applications, over concrete, first be treated with S-1300 Pene-Krete. Always refer to the Super-Krete Products Surface Preparation Guide for surface testing, cleaning, preparation and porosity requirements prior to application.

Super-Krete® Products is a Division of Arizona Polymer Flooring, Inc.

© 2017 Arizona Polymer Flooring, Inc
4565 W Watkins St. / Phoenix, AZ 85043 / 800.562.4921
623.435.2277 Tel. / 623.435.8585 Fax

www.super-krete.com

S-9350 Glo-Kote™ 032417



MIXING AND APPLICATION

Add water to S-9350 Glo-Kote to achieve a plaster-like consistency. The appropriate amount of water is necessary for S-9350 Glo-Kote to maintain the desired thickness. Do not over-dilute the product. Lightly mist the surface with clean water and apply S-9350 Glo-Kote mixture at a minimum 1/8" thickness using a cement trowel, screed rake or squeegee. Squeegees are recommended when applying large amounts at one time, but multiple applications will be required to obtain a minimum 1/8" thickness. For best results, first apply one application of S-9302 Bond-Kote® White as a base coat and allow to dry thoroughly.

S-9350 Glo-Kote must be applied in areas where there will be direct or indirect sunlight. The energizing of the glow is maximized by direct sunlight. Access to direct sunlight will yield a longer lasting and brighter glow. S-9350 Glo-Kote will reach its maximum charge rate from its light source in 2 hours (a light sub-surface will increase the glowing effect).

CURING TIME AND SEALING

Allow S-9350 Glo-Kote to cure a minimum of 24 hours in direct sunlight before sealing. Arizona Polymer Flooring recommends sealing all S-9350 Glo-Kote for wear and ease of maintenance. To determine the most appropriate sealer for your project, refer to the **Super-Krete Products Sealer Selection Guide**.

GENERAL INFORMATION

S-9350 Glo-Kote is ready-mixed and only requires the addition of water when mixing. This product requires no primer, bonding agents or cementitious underlayments to ensure a bond. S-9350 Glo-Kote cannot be removed from the concrete substrate once cured, without removing the substrate that it is attached to. This product is a high-strength product that is very resilient and durable.

Coverage Rates

5 sf at 1/8" (1 sf per pound)

**Coverage rates will vary, this is an approximation only. Actual coverage will vary due to substrate conditions, weather, surface porosity and method of application.*

Shelf Life 5 Years when properly stored.
Unopened and sealed

Storage Store in a cool, dry place.
Keep from moisture.

Packaging 5 lb. pail / 50 lb. pail
**(For volume purchasing, please call for pricing)*

Appearance White powdered form

Cure Time 24 hours

Odor None

Specific Gravity 3.15

**Percent Volatiles
by Volume** 0

Tools Required

3 gal. water sprayers
1/2" drill with mixing paddle attachment
5 gallon pails / 55 gallon drum / Plaster mixer
Trowel(s)

CAUTION

Keep away from children. Do not take internally. Always use safety gloves, appropriate eye protection, and appropriate OSHA/NIOSH approved respirator in areas with poor ventilation and when exposed to spray mist both indoors and outdoors. If ingested, seek medical attention immediately.

Super-Krete® Products is a Division of Arizona Polymer Flooring, Inc.

© 2017 Arizona Polymer Flooring, Inc
4565 W Watkins St. / Phoenix, AZ 85043 / 800.562.4921
623.435.2277 Tel. / 623.435.8585 Fax

www.super-krete.com

S-9350 Glo-Kote™ 032417



LIMITATIONS:

Super-Krete Products are to be applied only when surface temperatures are above 55°F and rising and not to exceed 100°F. Super-Krete Products are not to be applied when precipitation is expected within 24 hours following completion of application. Do not allow materials to freeze. Each Super-Krete product acts as an inherent part of a proven system. Super-Krete Products are professional, contractor grade products. Training in the use of these products is available. Consult a Super-Krete Products representative for information and assistance locating approved contractors in your area or for training class dates.

MOISTURE VAPOR EMISSIONS PRECAUTIONS:

All concrete floors not poured over an effective moisture vapor retarder are subject to possible moisture vapor transmission that may lead to blistering and failure of the coating system. It is the coating applicator's responsibility to conduct calcium chloride testing in compliance with ASTM F1869, or relative humidity probe testing in compliance with ASTM-F2170, to determine if excessive levels of vapor emissions are present before applying any coatings. Arizona Polymer Flooring offers **S-1300 Pene-Krete®** for cementitious overlay products and **VaporSolve® Moisture Remediation** systems for resinous floor coatings. Consult our technical service department. Arizona Polymer Flooring and its sales agents will not be responsible for coating failures due to undetected moisture vapor emissions.

WARRANTY:

Arizona Polymer Flooring guarantees that this product is free from manufacturing defects and complies with our published specifications. In the event that the buyer proves that the goods received do not conform to these specifications or were defectively manufactured, the buyer's remedies shall be limited to either the return of the goods and repayment of the purchase price or replacement of the defective material at the option of the seller. ARIZONA POLYMER FLOORING MAKES NO OTHER WARRANTY, EXPRESSED OR IMPLIED, AND ALL WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE HEREBY DISCLAIMED. Arizona Polymer Flooring shall not be liable for damages caused by application of its products over concrete with excessive moisture vapor transmission or alkalinity. Arizona Polymer Flooring shall not be liable for any injury incurred in a slip and fall accident. Manufacturer or seller shall not be liable for prospective profits or consequential damages resulting from the use of this product.

Super-Krete® Products is a Division of Arizona Polymer Flooring, Inc.

© 2017 Arizona Polymer Flooring, Inc

4565 W Watkins St. / Phoenix, AZ 85043 / 800.562.4921

623.435.2277 Tel. / 623.435.8585 Fax

www.super-krete.com

S-9350 Glo-Kote™ 032417

