

## SAFETY DATA SHEET

Page 1 of 6

### SECTION 1: IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY

#### MANUFACTURER'S NAME / ADDRESS

ARIZONA POLYMER FLOORING  
4565 W. WATKINS ST.  
PHOENIX, AZ 85043

TRADE NAME: VAPORSOLVE® JOINT FILLER PART B  
COLOR: CLEAR  
MAIN USE: SPECIALTY FLOORING CURATIVE

EMERGENCY TELEPHONE NUMBER: (800) 424-9300 (CHEMTREC)

### SECTION 2: HAZARDS IDENTIFICATION

#### GLOBALLY HARMONIZED SYSTEM (GHS)

##### CLASSIFICATION:

SKIN CORROSION: CATEGORY 1A

EYE DAMAGE: CATEGORY 1

SKIN SENSITIZATION: SUB-CATEGORY 1B

ACUTE TOXICITY, ORAL: CATEGORY 4

ACUTE TOXICITY, DERMAL: CATEGORY 4

AQUATIC TOXICITY: CATEGORY 3

#### GHS LABEL ELEMENTS

##### HAZARD PICTOGRAMS



SIGNAL WORD: DANGER!

#### HAZARD STATEMENTS

H302+H312: HARMFUL IN CONTACT WITH SKIN OR IF SWALLOWED

H314: CAUSES SEVERE SKIN BURNS AND EYE DAMAGE

H335: MAY CAUSE RESPIRATORY TRACT IRRITATION

H410: VERY TOXIC TO AQUATIC LIFE WITH LONG LASTING EFFECTS

#### PRECAUTIONARY STATEMENTS:

##### PREVENTION

P261: AVOID BREATHING DUST/FUME/GAS/MIST/VAPORS/SPRAY

P264: WASH SKIN THOROUGHLY AFTER HANDLING

P270: DO NOT EAT, DRINK OR SMOKE WHEN USING THIS PRODUCT

P280: WEAR PROTECTIVE GLOVES/ PROTECTIVE CLOTHING/ EYE PROTECTION/ FACE PROTECTION

##### RESPONSE

P303+P352: **IF ON SKIN:** WASH WITH PLENTY OF SOAP AND WATER

P305+P351+P338: **IF IN EYES:** RINSE CAUTIOUSLY WITH WATER FOR SEVERAL MINUTES. REMOVE CONTACT LENSES, IF PRESENT AND EASY TO DO SO. CONTINUE RINSING.

P304+P340 **IF INHALED:** REMOVE PERSON TO FRESH AIR AND KEEP COMFORTABLE FOR BREATHING

P301+P331: IF SWALLOWED: RINSE MOUTH. DO NOT INDUCE VOMITING

P337+P313: IF EYE IRRITATION PERSISTS: GET MEDICAL ADVICE/ATTENTION

P361+P364: TAKE OFF CONTAMINATED CLOTHING AND WASH BEFORE REUSE

# SAFETY DATA SHEET

VAPORSOLVE® JOINT FILLER PART B

Page 2 of 6

## SECTION 2: HAZARDS IDENTIFICATION CON'T.

### DISPOSAL

P501: DISPOSE OF CONTENTS/CONTAINER TO AN APPROVED WASTE DISPOSAL PLANT

### OTHER HAZARDS

NO DATA AVAILABLE

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

<u>HAZARDOUS INGREDIENTS</u>	<u>Wt. %</u>	<u>CAS Number</u>
PHENALKAMINE	10-30	868765-93-9
METHYLPENTAMETHYLENEDIAMINE	10-30	015520-10-2
BENZYL ALCOHOL	10-30	000100-51-6
EPOXY POLYAMINE ADDUCT	10-30	NOT AVAILABLE
SILICON DIOXIDE (AMORPHOUS)	1-5	112945-52-5

## SECTION 4: FIRST AID MEASURES

**GENERAL:** REMOVE PERSON FROM AFFECTED AREA AND MAKE COMFORTABLE. TREAT SYMPTOMATICALLY.

**EYES:** FLUSH WITH WATER FOR 15 MINUTES. GET MEDICAL ATTENTION.

**SKIN:** REMOVE PRODUCT AND FLUSH AFFECTED AREA WITH WATER FOR 15 MINUTES. IF IRRITATION PERSISTS GET MEDICAL ATTENTION.

**INHALATION:** MOVE TO FRESH AIR. GIVE ASSISTED RESPIRATION IF BREATHING HAS STOPPED OR IS LABORED (CALL A PHYSICIAN).

**INGESTION:** GIVE 3 – 4 GLASSES OF WATER OR MILK IF PERSON CONSCIOUS. **DO NOT INDUCE VOMITING!** OBTAIN MEDICAL CARE AND TREATMENT.

## SECTION 5: FIRE FIGHTING MEASURES

**FLASH POINT:** 121°C (250°F) – PMCC

**OSHA CLASS:** IIIB

**CONDITIONS OF FLAMMABILITY:** NA

**AUTO IGNITION TEMP.:** NA

**FLAMMABLE LIMITS:** LEL: NE UEL: NE

**SENSITIVITY TO IMPACT:** NONE

**HAZARDOUS COMBUSTION PRODUCTS:** CO, CO<sub>2</sub>, NH<sub>3</sub>, NITROGEN OXIDES CAN BE PRODUCED IF HEATED, BURNED OR REACTED WITH INCOMPATIBLE MATERIALS. NITROGEN OXIDES CAN REACT WITH WATER VAPORS TO FORM CORROSIVE NITRIC ACID.

**SENSITIVITY TO STATIC DISCHARGE:** NONE

**EXTINGUISHING MEDIA:** IGNITION MAY GIVE RISE TO A CLASS B FIRE. IN CASE OF FIRE USE: WATER FOG, CARBON DIOXIDE, DRY CHEMICAL, ALCOHOL FOAM.

**SPECIAL FIRE FIGHTING PROCEDURES:** NONE LIKELY WITH SMALL QUANTITIES. FOR LARGE QUANTITIES, FIREFIGHTERS AND OTHERS EXPOSED TO VAPORS OR PRODUCTS OF COMBUSTION SHOULD WEAR BUTYL RUBBER BOOTS, GLOVES AND BODY SUIT. SELF-CONTAINED BREATHING APPARATUS SHOULD BE WORN.

**UNUSUAL FIRE AND EXPLOSIVE HAZARDS:** MAY GENERATE TOXIC OR IRRITATING COMBUSTION PRODUCTS. SUDDEN REACTION AND FIRE MAY RESULT IF PRODUCT IS MIXED WITH AN OXIDIZING AGENT.

# SAFETY DATA SHEET

VAPORSOLVE® JOINT FILLER PART B

Page 3 of 6

## SECTION 6: ACCIDENTAL RELEASE MEASURES

**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:** SHUT OFF SOURCES OF IGNITION. COVER SPILLS WITH ABSORBENT. PLACE IN METAL CONTAINERS FOR RECOVERY OR DISPOSAL. PREVENT ENTRY INTO SEWERS, STORM DRAINS, AND WATERWAYS.

## SECTION 7: HANDLING AND STORAGE

**HANDLING:** AVOID CONTACT WITH SKIN AND EYES. EMERGENCY SHOWERS AND EYE WASH STATIONS SHOULD BE READILY ACCESSIBLE. ADHERE TO WORK PRACTICE RULES ESTABLISHED BY GOVERNMENT REGULATIONS. USE PERSONAL PROTECTIVE EQUIPMENT. WHEN USING DO NOT EAT, DRINK OR SMOKE.

**STORAGE:** KEEP AWAY FROM OXIDIZERS, HEAT OR FLAME. STORE IN STEEL CONTAINERS. DO NOT STORE NEAR ACIDS. KEEP CONTAINERS TIGHTLY CLOSED IN A DRY, COOL AND WELL-VENTILATED PLACE.

## SECTION 8: EXPOSURE CONTROL/PERSONAL PROTECTION

INGREDIENTS (CAS)	<u>EXPOSURE LIMITS (ppm)</u>				OTHER
	OSHA		ACGIH		
	TWA	STEL	TWA	STEL	
868765-93-9	NE	NE	NE	NE	
015520-10-2	NE	NE	NE	NE	
000100-51-6	NE	NE	NE	NE	
112945-52-5	NE	NE	NE	NE	

**LEGEND:** (M) MAX. EXPOSURE LIMIT; (S) OCCUPATIONAL EXP. LIMIT; (R) SUPPLIERS REC. LIMIT, (+) PERCUTANEOUS RISK  
NOTE 1: VALUES MEANINGFUL ONLY WHEN HARDENED PRODUCT IS ABRADED, GROUND, ETC.

**ENGINEERING CONTROLS:** NO SPECIFIC CONTROLS NEEDED. GENERAL AND LOCAL EXHAUST RECOMMENDED.

**RESPIRATORY PROTECTION:** NONE REQUIRED IN ADEQUATELY VENTILATED AREAS. IF VAPOR CONCENTRATION EXCEEDS 20ppm FOR LONGER THAN 15 MINUTES, A NIOSH APPROVED RESPIRATOR FOR ORGANIC VAPORS IS RECOMMENDED.

## SECTION 8: EXPOSURE CONTROL/PERSONAL PROTECTION

**PROTECTIVE GLOVES:** NITRILE RUBBER

**EYE PROTECTION:** SPLASH-PROOF GOGGLES OR CHEMICAL SAFETY GLASSES

**OTHER PROTECTIVE EQUIPMENT:** LONG SLEEVED SHIRTS AND TROUSERS. EMERGENCY SHOWERS AND EYE WASH STATIONS SHOULD BE READILY ACCESSIBLE.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

**BOILING POINT:** 260°C (500°F)

**SPECIFIC GRAVITY:** 0.95-1.05

**VAPOR PRESSURE:** ND

**MELTING POINT:** 0°C (32°F)

**VAPOR DENSITY:** ND  
(AIR = 1)

**EVAPORATION RATE:** ND  
(BUTYL ACETATE = 1)

**SOLUBILITY IN WATER:** <1%

**pH:** NE (ALKALINE)

**COEFFICIENT of WATER/OIL DISTRIBUTION:** ND

**ODOR THRESHOLD:** ND

**APPEARANCE AND ODOR:** AMBER LIQUID. AMMONIACAL ODOR.

**% VOLATILES BY VOLUME:** 0%

**%SOLIDS BY WEIGHT:** 100

# SAFETY DATA SHEET

VAPORSOLVE® JOINT FILLER PART B

Page 4 of 6

## SECTION 10: STABILITY AND REACTIVITY

**STABILITY:** STABLE

**CONDITIONS TO AVOID:** AVOID ELEVATED TEMPERATURES

**INCOMPATIBILITY (MATERIAL TO AVOID):** OXIDIZING AGENTS (PEROXIDES, NITRATES), ACIDS.

**HAZARDOUS DECOMPOSITION PRODUCTS:** NONE KNOWN

**HAZARDOUS POLYMERIZATION (REACTIVITY):** WILL NOT OCCUR

## SECTION 11: TOXICOLOGICAL INFORMATION

**LIKELY ROUTES OF EXPOSURE:** EYE CONTACT, SKIN CONTACT, INHALATION, INGESTION.

### EYES:

ACUTE – SEVERE IRRITANT. MAY CAUSE BURNS. VAPOR MAY CAUSE LACRIMATION AND REVERSIBLE CORNEAL EDEMA.

CHRONIC– CONJUNCTIVITIS OR CORNEAL DAMAGE.

### SKIN CONTACT:

ACUTE – UNDILUTED PRODUCT QUICKLY CAUSES IRRITATION. MAY CAUSE CHEMICAL BURNS.

CHRONIC – MAY CAUSE ALLERGIC REACTION/SENSITIZATION, DEFATTING OF SKIN, RASH AND IRRITATION.

### SKIN ABSORPTION:

ACUTE – ND

CHRONIC – ND

### INHALATION:

ACUTE – VAPORS MAY CAUSE DAMAGE TO CONTACTED TISSUE AND PRODUCE SCARRING.

CHRONIC- REPEATED AND/OR PROLONGED EXPOSURES CAN CAUSE TIGHTNESS OF CHEST, SHORTNESS OF BREATH AND COUGH.

### INGESTION:

ACUTE – MAY CAUSE IRRITATION AND BLEEDING OF THE GASTROINTESTINAL TRACT

CHRONIC – SCARRING OF THE AFFECTED TISSUES MAY OCCUR.

**ACUTE TOXICITY:** NO DATA ON THE PRODUCT ITSELF

### ACUTE ORAL TOXICITY- COMPONENTS

METHYLPENTAMETHYLENEDIAMINE LD50: 1690 mg/kg

SPECIES: RAT

BENZYL ALCOHOL

LD50: 1230 mg/kg

SPECIES: RAT

### ACUTE DERMAL TOXICITY- COMPONENTS

BENZYL ALCOHOL

LD50: 2000 mg/kg

SPECIES: RABBIT

### ACUTE INHALATION TOXICITY- COMPONENTS

METHYLPENTAMETHYLENEDIAMINE LC50 (4HR): > 4.9 mg/l

SPECIES: RAT

BENZYL ALCOHOL

LC50 (4HR): > 4.178mg/l

SPECIES: RAT

OECD TEST GUIDELINE 403

### SKIN CORROSION/IRRITATION

DOT SKIN CORROSION STUDY: CORROSIVE IN ALL RABBITS AT 3 MINUTES EXPOSURE

### SERIOUS EYE DAMAGE/EYE IRRITATION

SEVERE EYE IRRITATION

# SAFETY DATA SHEET

VAPORSOLVE® JOINT FILLER PART B

Page 5 of 6

## SECTION 11: TOXICOLOGICAL INFORMATION CON'T.

### SENSITIZATION

FOR SKIN SENSITIZATION:

MAY CAUSE AN ALLERGIC REACTION AFTER A SINGLE EXPOSURE OR WITH REPEATED OR PROLONGED SKIN CONTACT

FOR RESPIRATORY SENSITIZATION:

NOT CLASSIFIED BUT POSSIBLE DUE TO SKIN SENSITIZATION EFFECT

### SPECIFIC TARGET ORGAN SYSTEMIC TOXICITY (SINGLE EXPOSURE)

ND

### SPECIFIC TARGET ORGAN SYSTEMIC TOXICITY (REPEATED EXPOSURE)

ND

**CARCINOGENIC DATA: NTP:** NONE

**OSHA:** NONE

**IARC:** NONE

TERATOGENICITY: NO

MUTAGENICITY: NO

EMBRYOTOXICITY: NO

SYNERGISTIC MATERIAL: NO

## SECTION 12: ECOLOGICAL INFORMATION

### TOXICITY

**AQUATIC TOXICITY:** NO DATA ON THE PRODUCT ITSELF

#### ACUTE TOXICITY TO FISH- COMPONENTS

METHYLPENTAMETHYLENEDIAMINE

LC50 (96 HRS): 130 mg/l SPECIES: GOLDEN ORFE

BENZYL ALCOHOL

LC50 (96 HRS): 460 mg/l SPECIES: FATHEAD MINNOW

#### ACUTE TOXICITY TO AQUATIC INVERTEBRATES: COMPONENTS

METHYLPENTAMETHYLENEDIAMINE

EC50 (48 HRS): 10 mg/l SPECIES: DAPHNIA MAGNA

BENZYL ALCOHOL

EC50 (72 HRS): 12 mg/l SPECIES: DAPHNIA MAGNA

#### ACUTE TOXICITY TO ALGAE/AQUATIC PLANTS: COMPONENTS

METHYLPENTAMETHYLENEDIAMINE

EC50 (72 HRS): 10 mg/l SPECIES: FRESH WATER ALGAE

BENZYL ALCOHOL

EC50 (72 HRS): 700 mg/l SPECIES: FRESH WATER ALGAE

#### TOXICITY TO BACTERIA: COMPONENTS

ND

#### CHRONIC AQUATIC TOXICITY

ND

### PERSISTENCE AND DEGRADABILITY

**BIODEGRADABILITY:** BASED ON STRINGENT OECD TEST GUIDELINES, THIS MATERIAL CANNOT BE CONSIDERED READILY BIODEGRADABLE; HOWEVER, THESE RESULTS DO NOT NECESSARILY MEAN THAT THE MATERIAL IS NOT BIODEGRADABLE UNDER ENVIRONMENTAL CONDITIONS.

**BIODEGRADATION:** 29%

**EXPOSURE TIME:** 28 DAYS

**METHOD:** OECD TEST GUIDELINE 301B OR EQUIVALENT

## SECTION 12: ECOLOGICAL INFORMATION CON'T.

### BIOACCUMULATIVE POTENTIAL

**BIOACCUMULATION:** BIOCONCENTRATION POTENTIAL IS MODERATE (BCF BETWEEN 100 AND 3000 OR LOG P<sub>ow</sub> BETWEEN 3 AND 5)

**PARTITION COEFFICIENT:** N-OCTANOL/WATER (LOG P<sub>ow</sub>): 3.16 @21.5°C ESTIMATED

### MOBILITY IN SOIL

PRODUCT IS SOLUBLE IN WATER

**PARTITION COEFFICIENT (K<sub>oc</sub>):** 1.473 ESTIMATED

# SAFETY DATA SHEET

VAPORSOLVE® JOINT FILLER PART B

Page 6 of 6

## SECTION 13: DISPOSAL CONSIDERATIONS

**WASTE DISPOSAL METHODS:** INCINERATION IS PREFERRED. THIS PRODUCT SHOULD NOT BE ALLOWED TO ENTER DRAINS, WATER COURSES OR THE SOIL. PLACE IN AN APPROPRIATE DISPOSAL FACILITY IN COMPLIANCE WITH ALL FEDERAL, STATE AND LOCAL REGULATIONS.

## SECTION 14: TRANSPORT INFORMATION

**DOT PROPER SHIPPING NAME:**

AMINES, LIQUID, CORROSIVE, N.O.S. (METHYLPENTAMETHYLENEDIAMINE)

**HAZARD CLASS:** 8

**UN NUMBER:** UN 2735

**PACKING GROUP:** III

**IMO SHIPPING DATA:**

UN2735, AMINES, LIQUID, CORROSIVE, N.O.S. (METHYLPENTAMETHYLENEDIAMINE), 8, PG III

**ICAO/IATA SHIPPING DATA:**

UN2735, AMINES, LIQUID, CORROSIVE, N.O.S. (METHYLPENTAMETHYLENEDIAMINE), 8, PG III

## SECTION 15: REGULATORY INFORMATION

**VOC: COMPONENT:** 0 grams/Liter      **AS APPLIED:** 0 grams/Liter (PART OF MULTI-COMPONENT SYSTEM)

**TSCA (TOXIC SUBSTANCE CONTROL ACT):** ALL COMPONENTS ARE LISTED IN THE TSCA CHEMICAL SUBSTANCE INVENTORY.

**CERCLA (COMPREHENSIVE RESPONSE COMPENSATION and LIABILITY ACT):** ND

**SARA TITLE III**

**SECTION 312 HAZARD CLASS:** IMMEDIATE (ACUTE) HEALTH HAZARD, DELAYED (CHRONIC) HEALTH HAZARD

**SECTION 313 LISTED INGREDIENTS:** NONE

**CALIFORNIA PROPOSITION 65:** THE BELOW LIST OF COMPOUNDS IS KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER, BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM: NONE

## SECTION 16: OTHER INFORMATION

**INITIAL ISSUE DATE:** AUGUST 11, 2015

**REVISION DATE:**

**PREPARED BY:** J.W. ESSIG

**HAZARD RATING**

**HMIS:**                                      **HEALTH**    2                      **FLAMMABILITY**    1                      **REACTIVITY**    1

**LEGEND**

ACGIH:            AMERICAN CONFERENCE OF GOVERNMENTAL INDUSTRIAL HYGIENISTS  
OSHA:            OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION  
STEL:            SHORT TERM EXPOSURE LIMIT  
TWA:            TIME WEIGHTED AVERAGE  
PEL:            PERMISSIBLE EXPOSURE LIMIT  
TLV:            THRESHOLD LIMIT VALUE  
NA:            NOT APPLICABLE  
NE:            NOT ESTABLISHED  
ND:            NO DATA

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, express or implied, is made with respect to the accuracy of the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects, which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations and orders.